




NTN 22315UAVS2 thrust roller bearings



Bearing No. 22315UAVS2

22315UAVS2 Bearing 2D drawings and 3D CAD models

Size	75x160x55 mm
Bore Diameter	75,000 mm
Outer Diameter	160,000 mm
Width	55,000 mm
d	75,000 mm
D	160,000 mm
H	55,000 mm
Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	5.49
EAN	4547359270044
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch - Metric	Metric
Long Description	75MM Straight Bore; 160MM Outside Diameter;



LEA?Roller Industry Co.,Ltd

	55MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	12.089
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
Bore	2.953 Inch 75 Millimeter
Width	2.165 Inch 55 Millimeter
Outside Diameter	6.299 Inch 160 Millimeter
bore diameter:	75 mm
operating temperature range:	-40 to 120 ° C
outside diameter:	160 mm
cage material:	Brass
overall width:	55 mm
bearing material:	Through Hardened Steel
bore type:	Straight
cage type:	Machined
outer ring type:	Not Split
precision rating:	Not Rated
internal clearance:	Upper 2/3 of C4 range
finish/coating:	Uncoated
closure type:	Open
outer ring width:	55 mm
lubrication hole type:	Lubrication Groove & Hole



LEA?Roller Industry Co.,Ltd

inner ring width:	55 mm
dynamic load capacity:	335000 N
fillet radius:	2.5 mm
static load capacity:	320000 N
series:	223
maximum rpm:	2600 rpm
manufacturer product page:	Click here